



CUT LEVEL 9 HIGH-DEXTERITY NITRILE DIPPED GLOVES

HIGH DEXTERITY. MORE DURABLE.



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tearing	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

SMARTSWIPE™
Touch Screen
Compatible

Reinforced Nitrile Coating
Between Thumb & Forefinger

Long-Lasting Nitrile Grip



18 Gauge Knit
Total mobility

Light & Breathable Back

Color-Coded Bands
Easy cut level identification

SPECIFICATIONS

Gauge	18
Liner Material	HPPE-Tungsten-Nylon Blend
Dip Material	Sandy Nitrile
Cuff Style	Elasticated Knit

RECOMMENDED APPLICATIONS

- High Dexterity Applications
- Demolition
- Wire Stripping
- Tile Cutting
- Concrete Work
- Sheet Metal, Duct & Glass Handling

CARE INSTRUCTIONS

Machine wash warm water (105°F), mild detergent, no bleach. Line dry.

SIZE	1 PAIR	12 PAIR (Contractor Pack)
S	48-73-7030	48-73-7030B
M	48-73-7031	48-73-7031B
L	48-73-7032	48-73-7032B
XL	48-73-7033	48-73-7033B
XXL	48-73-7034	48-73-7034B

SEE MORE PPE



or visit <https://qr.mke.ti/2hz48>



Milwaukee®



Milwaukee®
A9
EN388
EN387
AK40F
SMARTSKIN™
48-73-1032
9" L
CUT LEVEL 9